

- 1 BFGoodrich® Tires Brand Logo
- 2 Free space for hot branding
- 3 Warning: provides user important safety information
- 4 LRG: Load Range/Ply Rating. In this case, Load Range G = 14 Ply Rating
- 5 USA Regulation Max. Load per Tire Single and Dual, Kg. and Lbs. Max. Pressure per Tire Single and Dual, kPa and psi.
- 6 Tread Design Name (DR454)
- 7 Tire Sizing: 11R22.5, 11 - Nomial Cross Section Width (in), R - Radial, 22.5 - Wheel Size (in)
- 8 Tire Construction. In this case, 4 steel plies in the tread, 1 steel ply in the sidewall
- 9 BFGoodrich® Tires Nomenclature: DR for drive, SI for steer, and TR for trailer
- 10 TUBELESS: Radial construction of the tire, no inner tube
- 11 REGROOVABLE: Only BFGoodrich® truck tires that are marked "REGROOVABLE" on the sidewall may be regrooved.
- 12 Manufacturing location: indicates where the tire was manufactured, in this case Canada
- 13 Department of Transportation (DOT) code, M53T - Plant Code
- 14 The last 4 numbers indicate the tire manufacturing date: Week 10, Year 2014
- 15 M+S: Mud and Snow Rating

